




Cam follower CFE18-UUR-IKO - CFE18-UUR-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cfe18-uur-iko>

IKO
CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Screwdriver Slot

CFE-UUR

| Outside diameter of eccentric roller mm | Identification number | | | | | Mass (Ref.) | | | |
|--|-------------------------|-----------------------------|-------------------------|-----------------------------|--|-------------|----|----|----------------|
| | Shield type | | Sealed type | | | Ø | D | C | d ₂ |
| | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | | | | | |
| 24 | | | CFE 18 UUR | | | 280 | 40 | 20 | 24 |

| Boundary dimensions mm | | | | | | | | | | Essentiality g | Mounting dimension f mm | Maximum tightening torque N·m | Basic dynamic load rating C N | Basic static load rating C ₀ N | Maximum allowable static load N |
|------------------------|----------------|----------|-----------------------|----------------|----------------|----------------|----------------|--------------|-----|-------------------|-------------------------------|--|--|--|--|
| G | B ₃ | B max | B ₁ max | B ₂ | C ₁ | g ₁ | G ₁ | (°) r/min | | | | | | | |
| M18×1.5 | 17.5 | 21.6 | 58.1 | 36.5 | 0.8 | 6 | 19 | 1 | 0.8 | 29 | 86.2 | 14 800 | 25 200 | 25 200 | |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3616060460011 |
| Inside diameter | 24 mm |
| Outside diameter | 40 mm |
| Thickness | 20 mm |
| Weight | 280 g |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE