


Cam follower CFE30-UUR-IKO - CFE30-UUR-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cfe30-uur-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Screwdriver Slot



Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		\emptyset	D	C	d_2
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
41			CFE 30	UUR	2 030	80	35	41

Boundary dimensions mm										Essentiality	Mounting dimension f Min. mm	Maximum tightening torque N-m	Basic dynamic load rating C N	Basic static load rating C_0 N	Maximum allowable static load N
G	B_3	B max	B_1 max	B_2	C_1	G_1	r_{max}	r_{min}	e						
M30x1.5	32.5	37	100	63	1	8	30.5	1	1.5	49	438	45 400	85 100	85 100	

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060460196
Inside diameter	41 mm
Outside diameter	80 mm
Thickness	35 mm
Weight	2030000 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE