

## Cam follower CFE10-1-VB-IKO - CFE10-1-VB-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cfe10-1-vb-iko>

IKO

### CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole



Outside diameter of outer ring mm	Identification number						Mass (Ref.)			
	Shield type			Sealed type			g	D	C	d <sub>e</sub>
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring						
13	CFE 10-1 VB						66	26	12	13

  

Boundary dimensions mm														
G	B <sub>3</sub>	B <sub>1</sub> max	B <sub>2</sub> max	C <sub>1</sub>	G <sub>1</sub>	H	f <sub>max</sub>	f <sub>min</sub>	Mounting dimension f mm	Maximum splining torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable static load N	
M10×1.25	10.5	13.2	36.2	23	0.6	—	12.5	4	0.3/0.4	16	13.8	9 570	14 500	8 650

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060460424
Inside diameter	13 mm
Outside diameter	26 mm
Thickness	12 mm
Weight	66 g
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE