

Cam follower CFE12-VB-IKO - CFE12-VB-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cfe12-vb-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole



Outside diameter of eccentric collar mm	Identification number						Mass (Ref.)			
	Shield type			Sealed type			Ø	D	C	d _e
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring						
16	CFE 12 VB						107	30	14	16

Boundary dimensions mm										
G	B ₃	B ₁ max	B ₂ max	B ₂	C ₁	G ₁	H	H _{max} (°)	f Min. mm	Mounting dimension g
M12×1.5	11.5	15.2	40.2	25	0.6	6	13.5	6	0.6/0.8	21

Mounting dimension f	Maximum splining torque	Basic dynamic load rating C	Basic static load rating C ₀	Maximum allowable static load
N·m	N	N	N	N
21.9	13 500	19 700	13 200	

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060460462
Inside diameter	16 mm
Outside diameter	30 mm
Thickness	14 mm
Weight	107 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE