


Cam follower CFE12-1-VBUU-IKO - CFE12-1-VBUU-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cfe12-1-vbuu-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole



CFE-VBUU

Outside diameter of eccentric collar mm	Identification number						Mass (Ref.)				
	Shield type			Sealed type			Ø	D	C	d _e	
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring							
16							CFE 12-1 VBUU	117	32	14	16

Boundary dimensions mm															
G	B ₃	B ₁ max	B ₂ max	B ₂	C ₁	G ₁	H	H _{max} (*)	Eccentricity e	f Min. mm	Mounting dimension Maximun splining torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N	
M12×1.5	11.5	15.2	40.2	25	0.6	6	13.5	6	0.6	0.8	21	21.9	13 500	19 700	13 200

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060460493
Inside diameter	16 mm
Outside diameter	32 mm
Thickness	14 mm
Weight	117 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE