

## Cam follower CFE10-VUUR-IKO - CFE10-VUUR-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cfe10-vuur-iko>

**IKO**  
**CAM FOLLOWERS**  
Eccentric Type Cam Followers **Full Complement Type/With Screwdriver Slot**

Outside diameter of eccentric outer ring mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		g	D	C	d <sub>e</sub>
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
<b>13</b>	<b>CFE 10 VUUR</b>				50.5	22	12	13

  

Boundary dimensions mm										Eccentricity E	Mounting dimension f Min. mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable static load N
G	B <sub>3</sub>	B max	B <sub>1</sub> max	B <sub>2</sub>	C <sub>1</sub>	g <sub>1</sub>	G <sub>1</sub>	r <sub>1</sub> min	r <sub>1</sub> max						
M10 × 1.25	10.5	13.2	36.2	23	0.6	*4	12.5	0.3	0.4	16	13.8	9 570	14 500	8 650	

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060460950
Inside diameter	13 mm
Outside diameter	22 mm
Thickness	12 mm
Weight	50.5 g
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE