


Cam follower CFE12-1-VUUR-IKO - CFE12-1-VUUR-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cfe12-1-vuur-iko>

IKO
CAM FOLLOWERS

Eccentric Type Cam Followers **Full Complement Type/With Screwdriver Slot**



Outside diameter of eccentric outer ring mm	Identification number				Mass (Ref.)				
	Shield type		Sealed type		g	D	C	d _e	
16	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					117
	CFE 12-1 VUUR								

Boundary dimensions mm														
G	B ₃	B		B ₂	C ₁	d ₁	G ₁	r _{1 min} (1)	Eccentricity E	Mounting dimension f Min. mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
		max	max											
M12 × 1.5	11.5	15.2	40.2	25	0.6	6	13.5	0.6	0.8	21	21.9	13 500	19 700	13 200

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060461070
Inside diameter	16 mm
Outside diameter	32 mm
Thickness	14 mm
Weight	117 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE