


## Cam follower CFE16-VUU-IKO - CFE16-VUU-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cfe16-vuu-iko>

IKO

**CAM FOLLOWERS**

Eccentric Type Cam Followers Full Complement Type/With Screwdriver Slot



CFE16-VUU

Outside diameter of eccentric outer ring mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		g	D	C	d <sub>e</sub>
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
22				CFE 16 VUU	193	35	18	22

Boundary dimensions mm														
G	B <sub>3</sub>	B <sub>max</sub>	B <sub>1</sub> <sub>max</sub>	B <sub>2</sub>	C <sub>1</sub>	g <sub>1</sub>	G <sub>1</sub>	r <sub>1</sub> <sup>(1)</sup> <sub>min</sub>	Eccentricity E	Mounting dimension f Min. mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable static load N
M16 × 1.5	15.5	19.6	52.1	32.5	0.8	6	17	0.6	0.8	26	58.5	20 700	37 600	23 200

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060461124
Inside diameter	22 mm
Outside diameter	35 mm
Thickness	18 mm
Weight	193 g
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE