

## Cam follower CFE24-VUU-IKO - CFE24-VUU-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cfe24-vuu-iko>

**IKO**  
**CAM FOLLOWERS**  
Eccentric Type Cam Followers Full Complement Type/With Screwdriver Slot

Outside diameter of eccentric collar mm	Identification number				Mass (Ref.) g	D	C	d <sub>e</sub>
	Shield type		Sealed type					
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
33				CFE 24 VUU	900	62	29	33

  

Boundary dimensions mm														
G	B <sub>3</sub>	B <sub>max</sub>	B <sub>1</sub> <sub>max</sub>	B <sub>2</sub>	C <sub>1</sub>	g <sub>1</sub>	G <sub>1</sub>	r <sub>1</sub> <sup>(1)</sup> <sub>min</sub>	Eccentricity E	Mounting diameter f Min. mm	Maximum operating torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable static load N
M24 × 1.5	25.5	30.6	80.1	49.5	0.8	8	24	1	0.8	40	215	46 800	92 000	52 000

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060461254
Inside diameter	33 mm
Inside diameter	1.299" inch
Outside diameter	62 mm
Outside diameter	2.441" inch
Thickness	29 mm
Thickness	1.142" inch
Weight	900 g
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE