


Cam follower CFE30-VUUR-IKO - CFE30-VUUR-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cfe30-vuur-iko>

IKO
CAM FOLLOWERS

Eccentric Type Cam Followers **Full Complement Type/With Screwdriver Slot**



Outside diameter of eccentric outer ring mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		g	D	C	d _e
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
41	CFE 30 VUUR				2 030	80	35	41

Boundary dimensions mm											Eccentricity E	Mounting dimension f Min. mm	Maximum operating torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
G	B ₃	B _{max}	B ₂ max	B ₂	C ₁	g ₁	G ₁	r ₁ min	r ₁ max	r ₁ min						
M30 × 1.5	32.5	37	100	63	1	8	30.5	1	1.5	49	438	67 700	144 000	85 900		

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060461322
Inside diameter	41 mm
Outside diameter	80 mm
Thickness	35 mm
Weight	2030 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE