


Cam follower CF-FU1-16-IKO - CF-FU1-16-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cf-fu1-16-iko>

IKO

CAM FOLLOWERS

Centralized Lubrication Type Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm				
	With crowned outer ring	With cylindrical outer ring		D	C	d ₁	G	G ₁
16		CF-FU1-16	170	35	18	16	M16 x 1.5	17

B _{max}	B _{1max}	B ₂	B ₃	C ₁	g ₂	M ₁	M ₂	f _{s min} ⁽¹⁾	Mounting dimension f Min. mm	Maximum tightening torque N-m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
19.6	52.1	32.5	8	0.8	3	PT 1/8	PT 1/8	0.6	26	58.5	12 000	18 300	18 300

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060461643
Inside diameter	16 mm
Outside diameter	35 mm
Thickness	18 mm
Weight	170 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE