


## Cam follower CF-FU1-30-1-IKO - CF-FU1-30-1-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cf-fu1-30-1-iko>

IKO

### CAM FOLLOWERS

Centralized Lubrication Type Cam Followers With Cage/With Screwdriver Slot



| Stud dia.<br>mm | Identification number      |                                | Mass<br>(Ref.)<br>g | Boundary dimensions mm |    |                |           |                |
|-----------------|----------------------------|--------------------------------|---------------------|------------------------|----|----------------|-----------|----------------|
|                 | With crowned<br>outer ring | With cylindrical<br>outer ring |                     | D                      | C  | d <sub>1</sub> | G         | G <sub>1</sub> |
| 30              |                            | <b>CF-FU1-30-1</b>             | 2 030               | 85                     | 35 | 30             | M30 x 1.5 | 32             |

| B <sub>max</sub> | B <sub>1max</sub> | B <sub>2</sub> | B <sub>3</sub> | C <sub>1</sub> | g <sub>2</sub> | M <sub>1</sub> | M <sub>2</sub> | f <sub>6</sub> min <sup>(1)</sup> | Mounting<br>dimension<br>f<br>Min.<br>mm | Maximum<br>tightening<br>torque<br>N·m | Basic dynamic<br>load rating<br>C<br>N | Basic static<br>load rating<br>C <sub>0</sub><br>N | Maximum<br>allowable<br>static load<br>N |
|------------------|-------------------|----------------|----------------|----------------|----------------|----------------|----------------|-----------------------------------|--|--|--|--|--|
| 37               | 100               | 63             | 15             | 1              | 4              | PT<br>1/8      | PT<br>1/8      | 1                                 | 49                                       | 438                                    | 45 400                                 | 85 100   | 85 100                                   |

## PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | IKO           |
| N° Ean13         | 3616060461766 |
| Inside diameter  | 30 mm         |
| Outside diameter | 85 mm         |
| Thickness        | 35 mm         |
| Weight           | 2030 g        |
| Packaging        | 1             |

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE