


Cam follower CR8-1-BUUR-IKO - CR8-1-BUUR-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cr8-1-buur-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Hexagon Hole



Stud dia. mm (inch)	Shield type				Sealed type		Mass (Ref.) g	D	C	d ₁	G UNF	G ₁
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring	g	D						
4.826							10	12.700 (1/2)	9.525 (3/8)	4.826	No.10-32	8.350 (1/2)

Boundary dimensions mm/inch											Bearing dimension f Mm (mm/inch)	Maximum tightening torque C N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
B max	B ₂	B ₃	C ₁	E ₁	E ₂	H	r							
10.9 (1/2)	15.875 (5/8)	- (-)	0.794 (1/8)	- (-)	- (-)	3.175 (1/4)	0.381 (1/64)	8.334 (1/2)	1.4	2.520	2.140			

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060462329
Inside diameter	4.826 mm
Outside diameter	12.7 mm
Thickness	9.525 mm
Weight	10 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE