


Cam follower CR18-BUUR-IKO - CR18-BUUR-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cr18-buur-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Hexagon Hole



Stud dia. mm (inch)	Identification number				g	D	C	d ₁	G UNF	G ₁
	Shield type With covered outer ring	Shield type With cylindrical outer ring	Sealed type With covered outer ring	Sealed type With cylindrical outer ring						
11.112 ($\frac{7}{16}$)	CR 18 BUUR				88	28.575 ($\frac{1}{2}$)	15.875 ($\frac{5}{8}$)	11.112 ($\frac{7}{16}$)	$\frac{5}{16}$ -20	12.700 ($\frac{1}{2}$)
Boundary dimensions mm/inch										
B max	B ₂	B ₃	C ₁	E ₁	E ₂	H	r	Bearing dimension f Mm/ mm(inch)	Maximum tightening torque C N·m	Basic static load rating C ₀ N
17.3 (0.68)	25.400 (1)	6.350 ($\frac{1}{4}$)	0.794 ($\frac{1}{32}$)	4.752 ($\frac{3}{16}$)	3.175 ($\frac{1}{8}$)	6.350 ($\frac{1}{4}$)	1.588 ($\frac{1}{16}$)	19.050 ($\frac{3}{4}$)	17.4	9 180

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060462527
Inside diameter	11.112 mm
Inside diameter	7/16" inch
Outside diameter	28.575 mm
Outside diameter	1 1/8" inch
Thickness	15.875 mm
Thickness	5/8" inch
Weight	88 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE