

Cam follower CR24-B-IKO - CR24-B-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cr24-b-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Hexagon Hole



Stud dia. mm (inch)	Identification number				Mass (Ref.)	Boundary dimensions mm (inch)						Bearing dimension <i>f</i> mm (inch)	Maximum tightening torque <i>C</i> N·m	Basic dynamic load rating <i>C</i> N	Basic static load rating <i>C₀</i> N							
	Shield type		Sealed type			<i>g</i>	<i>D</i>	<i>C</i>	<i>d₁</i>	<i>G</i>	<i>G₁</i>											
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring																		
15.875 ($\frac{5}{8}$)	CR 24 B				225	38.100 ($\frac{1 1/2}$)	22.225 ($\frac{7}{8}$)	15.875 ($\frac{5}{8}$)	$\frac{1}{2}$ -18	19.050 ($\frac{3}{4}$)	23.8 (0.93)	38.100 ($\frac{1 1/2}$)	9.525 ($\frac{3}{8}$)	0.794 ($\frac{1}{16}$)	4.702 ($\frac{1}{8}$)	3.969 ($\frac{1}{8}$)	7.938 ($\frac{1}{4}$)	1.588 ($\frac{1}{16}$)	26.196 (1.03)	55.7	19.600	24.300

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952460314
Inside diameter	15.875 mm
Outside diameter	38.1 mm
Thickness	22.225 mm
Weight	225 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE