


Cam follower CR26-B-IKO - CR26-B-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cr26-b-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Hexagon Hole



Stud dia. mm (inch)	Identification number				Mass (Ref.)	CR26-B					
	Shield type		Sealed type			g	D	C	d ₁	G UNF	G ₁
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring							
15.875 ($\frac{5}{8}$)	CR 26 B				260	41.275 ($\frac{1}{2}$)	22.225 ($\frac{1}{2}$)	15.875 ($\frac{5}{8}$)	$\frac{1}{2}$ -18	19.050 ($\frac{3}{4}$)	
Boundary dimensions mm(inch)											
B	B ₂	B ₃	C ₁	E ₁	E ₂	H	r	Bearing dimension f Mm (mm/inch)	Maximum tightening torque C N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
23.8 (0.93)	26.100 ($\frac{1}{2}$)	9.525 ($\frac{3}{8}$)	0.794 ($\frac{1}{16}$)	4.702 ($\frac{3}{16}$)	3.969 ($\frac{1}{8}$)	7.938 ($\frac{3}{8}$)	1.588 ($\frac{1}{16}$)	26.196 ($\frac{1}{2}$)	55.7	19 600	24 300

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060462626
Inside diameter	15.875 mm
Outside diameter	41.275 mm
Thickness	22.225 mm
Weight	260 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE