


Cam follower CR36-BUUR-IKO - CR36-BUUR-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cr36-buur-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Hexagon Hole



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	
	Shield type		Sealed type								
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring							
22.225 ($\frac{7}{8}$)	CR 36 BUUR				750	57.150 (2 $\frac{1}{4}$)	31.750 (1 $\frac{1}{4}$)	22.225 ($\frac{7}{8}$)	$\frac{7}{8}$ -14	25.400 (1)	
Boundary dimensions mm/inch											
B	B ₂	B ₃	C ₁	E ₁	E ₂	H	r	Bearing dimension f Mm/ mm(inch)	Maximum tightening torque C N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
33.5 (1.32)	50.800 (2)	12.700 ($\frac{1}{2}$)	0.794 ($\frac{1}{32}$)	4.762 ($\frac{3}{16}$)	4.762 ($\frac{3}{16}$)	11.112 ($\frac{7}{16}$)	1.588 ($\frac{1}{16}$)	31.306 (1 $\frac{1}{8}$)	152	32 500	63 000

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060462732
Inside diameter	22.225 mm
Inside diameter	7/8" inch
Outside diameter	57.15 mm
Outside diameter	2 1/4" inch
Thickness	31.75 mm
Thickness	1 1/4" inch
Weight	750 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE