


Cam follower CR16-IKO - CR16-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cr16-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁
	Shield type With covered outer ring	Shield type With cylindrical outer ring	Sealed type With covered outer ring	Sealed type With cylindrical outer ring						
11.112 ($\frac{7}{16}$)	CR 16				73	25.400 ($\frac{1}{16}$)	15.875 ($\frac{5}{16}$)	11.112 ($\frac{7}{16}$)	$\frac{1}{8}$ -20	12.700 ($\frac{1}{2}$)
Boundary dimensions mm(inch)										
B max	B ₂	B ₃	C ₁	S ₁	S ₂	r	Bearing dimension f Min. mm(inch)	Maximum tightening torque C	Basic dynamic load rating C ₀	Basic static load rating C ₀
17.3 0.68	25.400 ($\frac{1}{16}$)	6.350 ($\frac{1}{4}$)	0.794 ($\frac{1}{16}$)	4.762 ($\frac{3}{16}$)	3.175 ($\frac{1}{8}$)	1.591 ($\frac{1}{16}$)	17.859 ($\frac{9}{16}$)	17.4	8 910	10 800

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060462916
Inside diameter	11.112 mm
Outside diameter	25.4 mm
Thickness	15.875 mm
Weight	73 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE