

Cam follower CR10-V-IKO - CR10-V-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cr10-v-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Sealed type With shielded outer ring	Sealed type With cylindrical outer ring						
6.350 ($\frac{1}{4}$)		CR 10 V			19	15.875 ($\frac{5}{8}$)	10.319 ($\frac{3}{8}$)	6.350 ($\frac{1}{4}$)	$\frac{1}{4}$ -28	7.538 ($\frac{3}{8}$)
Boundary dimensions mm(inch)					Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N		
B max	B ₂	B ₃	C ₁	g ₁					g ₂	r
11.8.0.48	15.875 ($\frac{5}{8}$)	- (-)	0.794 ($\frac{1}{8}$)	*1.175 ($\frac{1}{8}$)	- (-)	0.367 ($\frac{1}{8}$)	11.508 ($\frac{9}{16}$)	3.4	5 800	7 880

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463241
Inside diameter	6.35 mm
Outside diameter	15.875 mm
Thickness	10.319 mm
Weight	19 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE