


Cam follower CR12-VBUUR-IKO - CR12-VBUUR-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cr12-vbuur-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers **With Cage/With Screwdriver Slot**



CR12-VBUUR

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Spigot type With groove outer ring	Spigot type With cylindrical outer ring							
9.525 ($\frac{3}{8}$)			CR 12	VBUUR	36	19.050 ($\frac{3}{4}$)	12.700 ($\frac{1}{2}$)	9.525 ($\frac{3}{8}$)	$\frac{1}{4}$ -24	9.525 ($\frac{3}{8}$)	
Boundary dimensions mm(inch)						Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N		
B max	B ₂	B ₃	C ₁	g ₁	g ₂					H	r
14.2 0.56	22.225 ($\frac{7}{8}$)	6.350 ($\frac{1}{4}$)	0.794 ($\frac{1}{32}$)	4.762 ($\frac{3}{16}$)	2.381 ($\frac{1}{8}$)	4.762 ($\frac{3}{16}$)	0.794 ($\frac{1}{32}$)	13.484 ($\frac{1}{2}$)	10.8	8 710	12 300

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463456
Inside diameter	9.525 mm
Outside diameter	19.05 mm
Thickness	12.7 mm
Weight	36 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE