


Cam follower CR14-VUUR-IKO - CR14-VUUR-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cr14-vuur-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.)					
	Shield type		Sleeved type		ϕ	D	C	d_1	G	G_1
	With cover	With cylindrical outer ring	With shielded outer ring	With cylindrical outer ring					UNF	
9.525 ($\frac{3}{8}$)			CR 14	VUUR	47	22.225 ($\frac{7}{8}$)	12.700 ($\frac{1}{2}$)	9.525 ($\frac{7}{8}$)	$\frac{1}{4}$ -24	9.525 ($\frac{7}{8}$)
Boundary dimensions mm(inch)					Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C_0 N		
B max	B_2	B_3	C_1	g_1					g_2	r
14.206	22.225 ($\frac{7}{8}$)	8.350 ($\frac{1}{2}$)	0.794 ($\frac{1}{4}$)	4.762 ($\frac{3}{8}$)	2.381 ($\frac{1}{4}$)	0.794 ($\frac{1}{4}$)	15.061 ($\frac{5}{8}$)	10.8	8 710	12 300

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463487
Inside diameter	9.525 mm
Outside diameter	22.225 mm
Thickness	12.7 mm
Weight	47 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE