


## Cam follower CR16-VB-IKO - CR16-VB-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cr16-vb-iko>

IKO

### CAM FOLLOWERS

Inch Series Cam Followers **With Cage/With Screwdriver Slot**



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d <sub>1</sub>	G UNF	G <sub>1</sub>	
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Shield type With groove outer ring	Shield type With cylindrical outer ring							
11.112 ( $\frac{7}{16}$ )		<b>CR 16 VB</b>			74	25.400 ( $\frac{1}{1}$ )	15.875 ( $\frac{3}{4}$ )	11.112 ( $\frac{7}{16}$ )	$\frac{3}{8}$ -20	12.700 ( $\frac{1}{2}$ )	
Boundary dimensions mm(inch)						Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N		
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	g <sub>1</sub>	g <sub>2</sub>					H	r
17.3 (0.68)	25.400 ( $\frac{1}{1}$ )	6.350 ( $\frac{1}{4}$ )	0.794 ( $\frac{1}{16}$ )	4.762 ( $\frac{3}{16}$ )	3.175 ( $\frac{1}{8}$ )	6.350 ( $\frac{1}{4}$ )	1.191 ( $\frac{1}{8}$ )	17.859 ( $\frac{3}{4}$ )	17.4	13 100	22 700

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463593
Inside diameter	11.112 mm
Outside diameter	25.4 mm
Thickness	15.875 mm
Weight	74 g
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE