

Cam follower CR20-V-IKO - CR20-V-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cr20-v-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inchi)	Identification number				Mass (Ref.)					
	Shield type		Sleeved type		g	D	C	d ₁	G	G ₁
	With covered outer ring	With cylindrical outer ring	With ribbed outer ring	With cylindrical outer ring				UNF		
12.700 (1/2)		CR 20 V			137	31.750 (1 1/4)	19.050 (3/4)	12.700 (1/2)	1-20	15.875 (5/8)
Boundary dimensions mm(inchi)					Mounting dimension f Min. mm(inchi)	Maximum tightening torque N·m	Basic dynamic load rating C	Basic static load rating C ₀		
B max	B ₂	B ₃	C ₁	g ₁					g ₂	r
28.4 (1.12)	31.750 (1 1/4)	7.938 (5/16)	0.794 (5/64)	4.762 (3/16)	3.175 (1/8)	1.588 (1/16)	21.828 (7/8)	27.7	23 800	31 700

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463715
Inside diameter	12.7 mm
Inside diameter	1/2" inch
Outside diameter	31.75 mm
Outside diameter	1 1/4" inch
Thickness	19.05 mm
Thickness	3/4" inch
Weight	137 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE