


Cam follower CR22-VUUR-IKO - CR22-VUUR-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cr22-vuur-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.)					
	Shield type		Splayed type		ϕ	D	C	d_1	G	G_1
	With covered outer ring	With cylindrical outer ring	With splayed outer ring	With cylindrical outer ring					UNF	
12.700 ($\frac{1}{2}$)			CR 22	VUUR	160	34.925 ($\frac{1}{2}$)	19.050 ($\frac{3}{4}$)	12.700 ($\frac{1}{2}$)	-20	15.875 ($\frac{5}{8}$)
Boundary dimensions mm(inch)					Mounting dimension f Min. mm(inch)	Maximum tightening torque C N·m	Basic dynamic load rating C_0 N	Basic static load rating C_0 N		
B max	B_2	B_3	C_1	g_1					g_2	r
28.4 (1.12)	21.750 ($\frac{1}{2}$)	7.938 ($\frac{5}{16}$)	8.794 ($\frac{5}{16}$)	4.762 ($\frac{3}{16}$)	3.175 ($\frac{1}{8}$)	1.588 ($\frac{1}{16}$)	21.628 ($\frac{5}{8}$)	27.7	22 800	31 700

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463807
Inside diameter	12.7 mm
Inside diameter	1/2" inch
Outside diameter	34.925 mm
Outside diameter	1 3/8" inch
Thickness	19.05 mm
Thickness	3/4" inch
Weight	160 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE