


Cam follower CR24-VB-IKO - CR24-VB-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cr24-vb-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers **With Cage/With Screwdriver Slot**



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G	G ₁	
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring							
15.875 ($\frac{5}{8}$)		CR 24 VB			230	38.100 ($\frac{1}{2}$)	22.225 ($\frac{7}{8}$)	15.875 ($\frac{5}{8}$)	$\frac{1}{4}$ -18	19.050 ($\frac{3}{4}$)	
Boundary dimensions mm(inch)						Mounting dimension f Min. mm(inch)	Maximum tightening torque N-m	Basic dynamic load rating C	Basic static load rating C ₀		
B max	B ₂	B ₃	C ₁	g ₁	g ₂					H	r
23.8 (0.93)	38.100 ($\frac{1}{2}$)	9.525 ($\frac{3}{8}$)	0.794 ($\frac{1}{16}$)	4.762 ($\frac{3}{16}$)	3.969 ($\frac{5}{32}$)	7.938 ($\frac{1}{2}$)	1.588 ($\frac{1}{16}$)	26.195 ($\frac{1}{2}$)	55.7	29 200	40 100

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463913
Inside diameter	15.875 mm
Outside diameter	38.1 mm
Thickness	22.225 mm
Weight	230 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE