

## Cam follower CR24-VBUUR-IKO - CR24-VBUUR-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cr24-vbuur-iko>

**IKO**

**CAM FOLLOWERS**

Inch Series Cam Followers **With Cage/With Screwdriver Slot**

CR24-VBUUR

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d <sub>1</sub>	G UNF	G <sub>1</sub>
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring						
15.875 (5/8)				CR 24 VBUUR	230	38.100 (1 1/2)	22.225 (7/8)	15.875 (5/8)	1/4-18	19.050 (3/4)

  

Boundary dimensions mm(inch)										Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	g <sub>1</sub>	g <sub>2</sub>	H	r						
23.8 (0.93)	38.100 (1 1/2)	9.525 (3/8)	0.794 (1/32)	4.762 (3/16)	3.969 (1/8)	7.938 (3/4)	1.588 (1/16)	26.195 (1 1/8)	59.7	29 200	40 100		

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463920
Inside diameter	15.875 mm
Inside diameter	5/8" inch
Outside diameter	38.1 mm
Outside diameter	1 1/2" inch
Thickness	22.225 mm
Thickness	7/8" inch
Weight	230 g
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE