

Cam follower CR36-V-IKO - CR36-V-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cr36-v-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.)					
	Shield type		Sleeved type		ϕ	D	C	d_1	G	G_1
	With cover	With cylindrical outer ring	With shielded outer ring	With cylindrical outer ring					UNF	
22.225 ($\frac{7}{8}$)		CR 36 V			759	57.150 (2 $\frac{1}{2}$)	31.750 (1 $\frac{1}{4}$)	22.225 (7/8)	$\frac{1}{2}$ -14	25.400 (1)

Boundary dimensions mm(inch)							Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
B max	B ₂	B ₃	C ₁	g_1	g_2	r				
33.5 (1.32)	33.800 (1)	12.700 ($\frac{1}{2}$)	8.794 ($\frac{5}{8}$)	4.762 ($\frac{3}{8}$)	4.762 ($\frac{3}{8}$)	1.588 ($\frac{1}{8}$)	31.368 (1 $\frac{1}{8}$)	162	45 700	80 800

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060464262
Inside diameter	22.225 mm
Outside diameter	57.15 mm
Thickness	31.75 mm
Weight	759 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE