


## Cam follower CR36-VBUUR-IKO - CR36-VBUUR-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cr36-vbuur-iko>

IKO

### CAM FOLLOWERS

Inch Series Cam Followers **With Cage/With Screwdriver Slot**



CR36-VBUUR

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d <sub>1</sub>	G UNF	G <sub>1</sub>	
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring							
22.225 ( <sup>7</sup> / <sub>16</sub> )			CR 36	VBUUR	759	57.150 (2 <sup>1</sup> / <sub>16</sub> )	31.750 (1 <sup>1</sup> / <sub>16</sub> )	22.225 (7 <sup>1</sup> / <sub>16</sub> )	7-14	25.400 (1)	
Boundary dimensions mm(inch)						Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N		
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	g <sub>1</sub>	g <sub>2</sub>					H	r
33.5 (1.32)	50.800 (2)	12.700 (1/2)	0.794 (1/32)	4.762 (3/16)	4.762 (3/16)	11.112 (7/16)	1.588 (1/16)	37.305 (1 1/8)	162	45 700	80 600

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060464316
Inside diameter	22.225 mm
Outside diameter	57.15 mm
Thickness	31.75 mm
Weight	759 g
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE