

## Cam follower CRH16-VBUU-IKO - CRH16-VBUU-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/crh16-vbuu-iko>

IKO

### CAM FOLLOWERS

Inch Series Heavy Duty Cam Followers Full Complement Type/With Hexagon Hole



CRH-VBUU

Stud dia. mm (inch)	Identification number		Mass (Ref.) g	D	C	d <sub>1</sub>	G UNF	G <sub>1</sub>	B max
	Shield type	Sealed type							
15.875 ( $\frac{5}{8}$ )	CRH 16	VBUU	93	25.400 (1)	15.875 ( $\frac{5}{8}$ )	15.875 ( $\frac{5}{8}$ )	$\frac{7}{16}$ -18	12.700 ( $\frac{1}{2}$ )	17.9 (0.70)

  

Boundary dimensions mm(inch)								Mounting dimension F Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N
B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	B <sub>1</sub>	B <sub>2</sub>	H	R					
25.400 (1)	6.350 ( $\frac{1}{4}$ )	1.588 ( $\frac{1}{16}$ )	4.762 ( $\frac{3}{16}$ )	2.381 ( $\frac{3}{32}$ )	6.350 ( $\frac{1}{4}$ )	1.191 ( $\frac{3}{32}$ )	18.256 ( $\frac{3}{4}$ )	57.8	13 100	22 700	

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060464484
Inside diameter	15.875 mm
Outside diameter	25.4 mm
Thickness	15.875 mm
Weight	93 g
Packaging	-

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE