


Cam follower CRH36-VUUR-IKO - CRH36-VUUR-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/crh36-vuur-iko>

IKO

CAM FOLLOWERS

Inch Series Heavy Duty Cam Followers Full Complement Type/With Screwdriver Slot



| Stud dia. mm (inch) | Identification number | | Mass (Ref.) g | D | C | d ₁ | G UNF | G ₁ | B max |
|---------------------------|-----------------------|-------------|---------------------|----------------|----------------|----------------|--------------------|----------------|-------------|
| | Shield type | Sealed type | | | | | | | |
| 28.575 (1 1/4) | CRH 36 | VUUR | 858 | 57.150 ± 0.025 | 31.750 ± 0.025 | 28.575 ± 0.025 | D ₁ -12 | 25.400 ± 0.025 | 34.2 ± 0.25 |

| Boundary dimensions mm(inch) | | | | | | | Mounting dimension f Min. mm(inch) | Maximum tightening torque N·m | Basic dynamic load rating C N | Basic static load rating C ₀ N |
|------------------------------|----------------|----------------|----------------|----------------|-------------|----------------|--|--|--|--|
| B ₂ | B ₃ | C ₁ | S ₁ | S ₂ | R | | | | | |
| 50.800 ± 0.025 | 12.700 ± 0.025 | 1.588 ± 0.025 | 4.762 ± 0.025 | 3.175 ± 0.025 | 600 ± 0.025 | 37.306 ± 0.025 | 356 | 45 700 | 80 600 | |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952463889 |
| Inside diameter | 28.575 mm |
| Outside diameter | 57.15 mm |
| Thickness | 31.75 mm |
| Weight | 858 g |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE