


Cam follower CRH56-VBUUR-IKO - CRH56-VBUUR-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/crh56-vbuur-iko>

IKO

CAM FOLLOWERS

Inch Series Heavy Duty Cam Followers Full Complement Type/With Hexagon Hole



Stud dia. mm (inch)	Identification number		Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	B max
	Shield type	Sealed type							
44.450 (1.75)	CRH 56	VBUUR	3240	88.900 (3.5)	50.800 (2)	44.450 (1.75)	1 7/8-10UN	34.925 (1.375)	52.8 (2.08)

Boundary dimensions mm(inch)								Mounting dimension F mm (inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
B ₂	B ₃	C ₁	B ₁	B ₂	H	R					
69.850 (2.75)	17.462 (0.6875)	1.588 (0.0625)	6.350 (0.25)	3.175 (0.125)	19.050 (0.75)	760 (30)	59.928 (2.3575)	1.450	111 000	229 000	

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952464251
Inside diameter	44.45 mm
Outside diameter	88.9 mm
Thickness	50.8 mm
Weight	3240 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE