


Roller bearing NQI20-12-JTEKT - NQI20-12-KOYO

<https://www.123bearing.com/bearing-housing/roller-bearing/roller/nqi20-12-koyo>

Machined ring needle roller bearings Koyo

F_w 29 – 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.	
F_w	d	D	B	B_1	r (mm)	C_r	C_{10}	Oil lub.	Without inner ring	Without inner ring
24	20	32	12	—	0.3	9.6	14.4	19 000	—	—
				Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.	
				With inner ring	d_w min.	D_w max.	r_w max.	Without inner ring	With inner ring	Applicable inner ring No.
				NQI20/12	22	30	0.3	0.025	0.038	—

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952482309
Inside diameter	20 mm
Outside diameter	32 mm
Thickness	12 mm
Weight	38 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE