


## Roller bearing NA5920-JTEKT - NA5920-KOYO

<https://www.123bearing.com/bearing-housing/roller-bearing/roller/na5920-koyo>

Machined ring needle roller bearings ————— **Koyo**  
F<sub>W</sub> 29 ~ 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.	
F <sub>w</sub>	d	D	B	B <sub>1</sub>	C <sub>r</sub>	C <sub>10</sub>	Oil lub.		Without inner ring	
115	100	140	54	—	189.0	418.0	4 000	—	—	
Mounting dimensions (mm)					(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring					d <sub>1</sub> min.	D <sub>1</sub> max.	r <sub>1</sub> max.	Without inner ring	With inner ring	IRM1001554
<b>NA5920</b>					106.5	133.5	1	1.49	2.53	

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952484242
Inside diameter	100 mm
Outside diameter	140 mm
Thickness	54 mm
Weight	2530 g
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE