


Axial needle roller AZ457320-IKO - AZ457320-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/axial-needle/az457320-iko>

IKO

THRUST BEARINGS

Thrust Roller Bearings



Shaft dia. mm	Identification number							
	Thrust roller bearing	Mass (Ref.) g	Thrust roller bearing	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g	
45	AZ 457320	360	AZK 45739	144	WS 4573	GS 4573	108	

Boundary dimensions mm										Standard mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾
d	D	T	d _c	D _c	D _w	B	r _s (1)	C ₁	C ₂	d _s Min.	D _s Max.	N	N	rpm
45	73	20	45.05	72.5	9	5.5	1	50	69	69	51	75 700	227 000	5 000

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060465979
Inside diameter	45 mm
Outside diameter	73 mm
Thickness	20 mm
Weight	360 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE