


## Axial needle roller AZK6013010-IKO - AZK6013010-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/axial-needle/azk6013010-iko>

**IKO**  
**THRUST BEARINGS**

Thrust Roller Bearings



Shaft dia. mm	Identification number							
	Thrust roller bearing	Mass (Ref.) g	Thrust roller bearing	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g	
60	<b>AZ 6013026</b>	2 090	<b>AZK 6013010</b>	790	<b>WS 60130</b>	<b>GS 60130</b>	660	

Boundary dimensions mm										Standard mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup>
d	D	T	d <sub>c</sub>	D <sub>c</sub>	D <sub>w</sub>	B	r <sub>s</sub> (1)	C <sub>1</sub>	C <sub>2</sub>	d <sub>s</sub> Min.	D <sub>s</sub> Max.	N	N	rpm
60	130	26	60.05	129.5	10	8	1.5	79	119	119	80	158 000	634 000	3 000

Notes: (1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060466075
Inside diameter	60 mm
Outside diameter	130 mm
Thickness	10 mm
Weight	790 g
Packaging	-
Standard	-

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE