

SI Rod end SI10-T-K-DURBAL - SI10-T-K-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/si10-t-k-durbal>


SI10-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SI 10 TIK		10	M 10	14	10,50	28	15,0	19

type	measurement [mm]			h	d ₁	load rating C ₀ [N]	weight [kg]
	l ₁ min	W					
SI / SIL 10 TIK	20	17		43	13	18,0	0,077

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489209
Inside diameter	10 mm
Inside diameter	0.394" inch
Outside diameter	28 mm
Outside diameter	1.102" inch
Thickness	14 mm
Thickness	0.551" inch
Type	SI
Weight	77 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE