

SI Rod end SIL14-T-K-DURBAL - SIL14-T-K-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/sil14-t-k-durbal>


SIL14-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	measurement (mm)
right hand thread left hand thread SIL 14 T/K	d 14 G M 14 B 19 C1 13,50 d2 36 d3 20,0 d4 25

type	measurement (mm)			load rating C ₀ (N)	weight (kg)
	l ₁ min	W	h		
SI / SIL 14 T/K	25	22	57	16	31,0

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489339
Inside diameter	14 mm
Outside diameter	36 mm
Thickness	19 mm
Type	SI
Weight	160 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE