

SI Rod end SI20-T-K-DURBAL - SI20-T-K-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/si20-t-k-durbal>


SI20-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SI 20 TIK		20	M 20 x 1,5	25	18,00	50	27,5	34

type	measurement [mm]			d ₁	load rating C ₀ [N]	weight [kg]
	l ₁ min	W	h			
SI / SIH 20 TIK	33	30	77	14	57,0	0,420

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489537
Inside diameter	20 mm
Inside diameter	0.787" inch
Outside diameter	50 mm
Outside diameter	1.969" inch
Thickness	25 mm
Thickness	0.984" inch
Type	SI
Weight	420 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE