

SI Rod end SIL22-T-K-DURBAL - SIL22-T-K-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/sil22-t-k-durbal>


SIL22-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SIL 22 T/K			22	M 22 x 1,5	28	20,00	54	30,0	38

type	measurement (mm)			d ₁	load rating C ₀ (N)	weight (kg)
	l ₁ min	W	h			
SI / SIL 22 T/K	37	32	84	15	68,0	0,540

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489575
Inside diameter	22 mm
Outside diameter	54 mm
Thickness	28 mm
Type	SI
Weight	540 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE