

SI Rod end SI28-T-K-DURBAL - SI28-T-K-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/si28-t-k-durbal>


SI28-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SI 28 TIK			28	M 27 x 2	35	24,00	66	37,0	46

type	measurement (mm)			d PT	load rating C ₀ (N)	weight (kg)
	l ₁ min	W	h			
SI / SI128 TIK	51	41	103	15	107,0	0,820

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489681
Inside diameter	28 mm
Outside diameter	66 mm
Thickness	35 mm
Type	SI
Weight	820 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE