

## SI Rod end SIL30-T-K-DURBAL - SIL30-T-K-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/sil30-t-k-durbal>


### SIL30-T-K



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / bronze-PTFE composite

**Inner ring:**  
bearing steel, hardened, ground and  
spherical surface chromium plated

**Outer ring:**  
brass body pressed around, outer race  
lined with bronze-PTFE composite

**Lubrication:**  
maintenance free

order number	right hand thread	left hand thread	measurement [mm]						
SIL 30 T/K			d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
			30	M 30 x 2	37	25,00	70	40,0	50

type	measurement [mm]			h	d <sub>1</sub> PT	load rating C <sub>0</sub> [N]	weight [kg]
	l <sub>1</sub> min	W					
SI / SIL 30 T/K	51	41	110	17	114,0	1,100	

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489728
Inside diameter	30 mm
Inside diameter	1.181" inch
Outside diameter	70 mm
Outside diameter	2.756" inch
Thickness	37 mm
Thickness	1.457" inch
Type	SI
Weight	1100 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE