

SI Rod end SI35-T-K-DURBAL - SI35-T-K-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/si35-t-k-durbal>


SI35-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SI 35 TIK		35	M 36 x 2	43	28,00	81	46,0	58

type	measurement [mm]			load rating C ₀ [kN]	weight [kg]
	l ₃ min	W	h		
SI / SI35 TIK	56	50	125	16	1,600

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489773
Inside diameter	35 mm
Outside diameter	81 mm
Thickness	43 mm
Type	SI
Weight	1600 g
Thread	Right-hand thread
Lubrication	without
Packaging	1
Standard	No standard

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE