

# SI Rod end SIL35-T-K-DURBAL - SIL35-T-K-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/sil35-t-k-durbal>


## SIL35-T-K



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / bronze-PTFE composite

**Inner ring:**  
bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:**  
brass body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:**  
maintenance free

order number	right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SIL 35 T/K			35	M 36 x 2	43	28,00	81	46,0	58

type	measurement (mm)			h	d1 PT	load rating C0 (kN)	weight (kg)
	l1 min	W					
SI / SIL 35 T/K	56	50	125	16			1,600

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489803
Inside diameter	35 mm
Inside diameter	1.378" inch
Outside diameter	81 mm
Outside diameter	3.189" inch
Thickness	43 mm
Thickness	1.693" inch
Type	SI
Weight	1600 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE