

SI Rod end

SIL50-T-K-DURBAL - SIL50-T-K-DURBAL

https://www.123bearing.com/bearing-housing/rod-end/si/sil50-t-k-durbal


SIL50-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
	SIL 50 T/K	50	M 48 x 2	60	45,00	117	65,0	75

type	measurement [mm]			d ₁ PT	load rating C ₀ [kN]	weight [kg]
	l ₃ min	W	h			
SI / SIL 50 T/K	65	65	160	12		5,000

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489889
Inside diameter	50 mm
Outside diameter	117 mm
Thickness	60 mm
Type	SI
Weight	5000 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE