

**SA Rod end**  
**SAL8-T-K-DURBAL - SAL8-T-K-DURBAL**  
<https://www.123bearing.com/bearing-housing/rod-end/sa/sal8-t-k-durbal>

**SAL8-T-K**



**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

**male thread:** maintenance free, according to DIN ISO 12240-4, series K

**Rod end body:** surface zinc plated

**Sliding combination:** steel / bronze-PTFE composite

**Inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** brass body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** maintenance free

order number		measurement [mm]		Tragzahlen		weight
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>
SAL 8 T/K		8	M 8	12	9,00	24

  

type	measurement [mm]		h	α [°]	Tragzahlen C <sub>10</sub> [kN]	weight [kg]
	l <sub>1</sub> min	l <sub>2</sub>				
SA / SAL 8 T/K	25		42	14	12,9	0,038

**PRODUCT FEATURES**

Brand	DURBAL
N° Ean13	3663952490007
Inside diameter	8 mm
Outside diameter	24 mm
Thickness	12 mm
Type	SA
Weight	38 g
Thread	Left-hand thread
Lubrication	without
Packaging	-
Standard	No standard

[contact@123bearing.com](mailto:contact@123bearing.com)  
(646) 712 9672  
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE