

SA Rod end
SAL16-T-K-DURBAL - DSAL16-T-K-DURBAL
<https://www.123bearing.com/bearing-housing/rod-end/sa/dsal16-t-k-durbal>

SAL16-T-K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

male thread: maintenance free, according to DIN ISO 12240-4, series K

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	measurement [mm]		C ₁	d ₂
	right hand thread	left hand thread		
SAL 16 T/K	16	M 16	21	15,00

type	measurement [mm]		h	α [°]	Tragzahlen C ₁₀ [kN]	weight [kg]
	l ₁ min	l ₂				
SA / SAL 16 T/K	37	21	66	15	39,0	0,210

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952490168
Inside diameter	16 mm
Outside diameter	42 mm
Thickness	21 mm
Type	SA
Weight	210 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE