

SA Rod end
SAL20-T-K-DURBAL - SAL20-T-K-DURBAL
<https://www.123bearing.com/bearing-housing/rod-end/sa/sal20-t-k-durbal>

SAL20-T-K



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series K

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	measurement [mm]		C ₁	d ₂
	right hand thread	left hand thread		
SAL 20 T/K	20	M 20 x 1,5	25	18,00

type	measurement [mm]				Tragzahlen C ₁₀ [KN]	weight [kg]
	l ₁ min	l ₂	h	α [°]		
SA / SAL 20 T/K	45	25	78	14	57,0	0,380

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952490243
Inside diameter	20 mm
Outside diameter	50 mm
Thickness	25 mm
Type	SA
Weight	380 g
Thread	Left-hand thread
Lubrication	without
Packaging	1
Standard	No standard

contact@123bearing.com
(646) 712 9672
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE