

SA Rod end
SAL22-T-K-DURBAL - SAL22-T-K-DURBAL
<https://www.123bearing.com/bearing-housing/rod-end/sa/sal22-t-k-durbal>

SAL22-T-K



male thread; maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
	SAL 22 T/K	22	M 22 x 1,5	28	20,00	54

type	measurement [mm]		h	α [°]	Tragzahlen C ₁₀ [kN]	weight [kg]
	l ₁ min	l ₂				
SA / SAL 22 T/K	48	27	84	15	68,0	0,480

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952490250
Inside diameter	22 mm
Outside diameter	54 mm
Thickness	28 mm
Type	SA
Weight	480 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com
(646) 712 9672
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE