

SA Rod end
SAL40-T-K-DURBAL - SAL40-T-K-DURBAL
<https://www.123bearing.com/bearing-housing/rod-end/sa/sal40-t-k-durbal>

SAL40-T-K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

male thread: maintenance free, according to DIN ISO 12240-4, series K

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	measurement [mm]		C ₁	d ₂	
	right hand thread	left hand thread			
SAL 40 T/K	40	M 42 x 2	49	33,00	91

type	measurement [mm]		h	α [°]	Tragzahlen C ₁₀ [KN]	weight [kg]
	l ₁ min	l ₂				
SA / SAL 40 T/K	90	46	150	17		2,300

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952490489
Inside diameter	40 mm
Outside diameter	91 mm
Thickness	49 mm
Type	SA
Weight	2300 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.com
(646) 712 9672
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE