

**SA Rod end**  
**SA50-T-K-DURBAL - SA50-T-K-DURBAL**  
<https://www.123bearing.com/bearing-housing/rod-end/sa/sa50-t-k-durbal>


**SA50-T-K**



male thread;  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE composite

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
brass body pressed around, outer race  
lined with bronze-PTFE composite

Lubrication:  
maintenance free

order number	measurement [mm]				
	d	G	B	C <sub>1</sub>	d <sub>2</sub>
SA 50 T/K	50	M 48 x 2	60	45,00	117

type	measurement [mm]			Tragzahlen C <sub>10</sub> [kN]	weight [kg]
	l <sub>1</sub> min	l <sub>2</sub>	h		
SA / SAL 50 T/K	105	59	185	12	4,800

**PRODUCT FEATURES**

Brand	DURBAL
N° Ean13	3663952490526
Inside diameter	50 mm
Outside diameter	117 mm
Thickness	60 mm
Type	SA
Weight	4800 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE